


SNS

	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	mass kg	load cg mm	scraper	side positions l/r
SNS R 1500	1000	1555	705	-	1500	420	200	80	190	1200	rubber	30/45°
SNS V 1500	1000	1555	705	-	1500	420	200	80	190	1200	vulkollan	30/45°
SNS R 1800	1000	1555	705	-	1800	420	200	80	206	1220	rubber	30/45°
SNS V 1800	1000	1555	705	-	1800	420	200	80	206	1220	vulkollan	30/45°
SNS R 2000	1000	1555	705	-	2100	420	200	80	225	1240	rubber	30/45°
SNS V 2000	1000	1555	705	-	2100	420	200	80	225	1240	vulkollan	30/45°
SNS R 2400	1000	1555	705	-	2400	420	200	80	250	1260	rubber	30/45°
SNS V 2400	1000	1555	705	-	2400	420	200	80	250	1260	vulkollan	30/45°

DETAILS



Scraper blades
Schuiflijsten
Schubränder
Rascadores



Scraper blade adjustable
Schuifblad verstelbaar
Verstellbarer Planierschild
Hoja rascadora ajustable



Fixing
Bevestiging
Befestigung
Mecanismo de fijación



Removable scraper blades
Demontabele schuiflijsten
Demontierbare Schubränder
Rascadores desmontables



Angular adjustment
Hoekverstelling
Winkeleinstellung
Ajuste de ángulo



- Most common scraper for light and heavy material, with an adjustable scraper blade



- Gängigstes Planiergerät für leichtes und schweres Material mit verstellbarem Planierschild



- Meest gangbare schuiver voor licht en zwaar materiaal, met verstelbaar schuifblad



- La pala más usual para materiales livianos y pesados, con hoja rascadora ajustable